

V-LINE DATA SHEET



VECTOR SPORTS DATA

C/ Arístides Maillol, 7, C2 2ª 08028 Barcelona - España +34 657 264 676 info@vector.com.es www.vector.com.es

1. DESCRIPCIÓN

This is the white covering in waterborne of acrylic nature that usually serves to mark the lines during the tennis courts creation. It is characteristic for high impact resistance, outdoor solidity and abrasion resistance. It contains an important grade of compaction in order to generate solid and resistant first layer.

Moreover, it contains high wear resistance, toughness and durability. It is indicated specifically for the line marking on tennis courts and multisport surfaces.

General characteristics

- Nontoxic and no inflammable product.
- Impermeable.
- High level of abrasion.
- Slip resistant.

2. FIELDS/AREAS OF APPLICATION

This product is designed for marking the lines.

3. SURFACE PREPARATION

The previous V-TOP layer will be completely dry. Moreover, it will be clean, dust, grease and other odd materials exempt.

4. CONDITIONS OF APPLICATIONS

The ideal weather conditions for the application will be dry and between 10 and 30 °C. It is not recommendable to apply the product when raining.

5. APPLICATION

Before applying the product it is necessary to ensure the complete homogenization of the product. Apply with brush or roller.

The estimated time of the drying process of each and every layer is more or less 12 hours, depends on the overall temperature and the overall grade of humidity.

Precaution



It is not resistant to fuel.

Storage

The containers shall be stored perfectly closed and sheltered in indoor conditions, in places protected from frost and strong sun exposure. Temperatures below 5 ° C can affect product quality. The products can be kept for one year in their original drums, tightly closed and undamaged.

6. TECHNICAL SPECIFICATIONS

| Density at 25 ºC | 1,35 - 1.45 g/cm ³ |
|-------------------------------|-------------------------------|
| Viscosity Brookfield at 25 ºC | 32000 - 36000 |
| Solids in volume | 65 - 67 % |
| Solids in weight | 75 - 77 % |
| Theoretical coverage | 2,1 g/m² |

This information replaces the previous ones. The specifications and technical data that appear in this sheet are indicative. Vector Sports reserves the right to modify them without prior notice and disclaims any liability for misuse.